



⑤	TERM	TIN-PLATED,16# MOLEX: 39000081	5	PCS				
④	HSG	5P,4.2PH,WHITE,HF MOLEX: 39014057	1	PCS				
③	TERM	TIN-PLATED,16# MOLEX: 39000077	5	PCS				
②	HSG	5P,4.2PH,WHITE,HF MOLEX: 39014051	1	PCS				
①	WIRE	UL1430 16#/5C Flat Cable,Wire Color:1pcs Gray+4pcs White (See Wiring Diagram)	A/R	MM				
NO.	PART NAME	DESCRIPTION	Q'TY	UNIT				

Wiring Diagram				
Define	P1	COLOR	P2	Define
GND	1	White	1	GND
ADD	2	White	2	ADD
DMX+	3	White	3	DMX+
DMX-	4	White	4	DMX-
24V+	5	Gray	5	24V+

Voltage Rating: DC300V 0.1 Sec.
Current Rating: 9 A
Insulation Resistance: ≥10 MΩ
Conduction Resistance: ≤5 Ω
Compliance with ROHS

Technical Parameters:

TRAAXION | eCcue

Product Name: TX CONNECT Smart 0.5/1/3/5/10m Mini (SFemale) to Mini (SMale) Extension Cable

Product Part Number:

Project Name:

Drawing Title:

Location:

Date:

Drawing Notes

Scale: SCALE

Troxon Technologies and eCcue Lighting control reserves the right to make changes to this information at any time.
All of the information contained in these drawings is diagrammatic in nature and is not to be used for construction.
Refer to applicable architectural and engineering drawings for fixture placement, wire and conduit paths, junction box placements, etc.