



**Technical Parameters:**

Voltage Rating: DC300V 0.1 Sec.

Current Rating: 9 A

Insulation Resistance: ≥10 MΩ

Conduction Resistance: ≤5 Ω

Compliance with ROHS

⑨	TUBE	HS TUBE WHITE	A/R	MM					
⑧	TERM	Soldering 3 Wires Together	1	PCS					
⑦	HSG	4P,4.2PH,WHITE,HF MOLEX: 39014047	1	PCS					
⑥	TERM	TIN-PLATED,16# MOLEX: 39000081	6	PCS					
⑤	HSG	5P,4.2PH,WHITE,HF MOLEX: 39014057	1	PCS					
④	TERM	TIN-PLATED,16# MOLEX: 39000077	5	PCS					
③	HSG	5P,4.2PH,WHITE,HF MOLEX: 39014051	1	PCS					
②	WIRE	UL1430 16# Wire,Wire Color:1pcs Gray+1pcs White(See Wiring Diagram)	A/R	MM					
①	WIRE	UL1430 16#4C Flat Cable,Wire Color:4pcs White(See Wiring Diagram)	A/R	MM					
NO.	PART NAME	DESCRIPTION	Q'TY	UNIT					

Wiring Diagram									
Define	P1	COLOR	P2	Define	COLOR	P3	COLOR	Define	
GND	4	White	1	GND	White	1	White	GND	
	-	-	2	ADD	White	2	White	ADD	
	-	-	3	DMX+	White	3	White	DMX+	
	-	-	4	DMX-	White	4	White	DMX-	
	24V+	Gray	5	24V+	Gray	5	-	-	

TRAxON | eCue

Product Name: TX CONNECT Smart Power Injector Cable for PXL Board RGB30

Project Name:

Product Part Number:

Drawing Title:

Location:

Date:

Drawing Notes

