



LUXPOINT® LED Batten - Dalbert

Datasheet



CE UK CA IP54 IK06

The Dalbert series LED batten is elongated, linear lighting fixtures designed for practical, energy-efficient and uniform illumination in a variety of commercial and industrial spaces. With a slim profile, integrate design and various lengths, The Dalbert series provide flexible, customizable solutions included shopping centers, warehouse, workshops and other public lighting areas. The Dalbert series have consistent, high-quality and uniform light output to deliver impressive efficiency, long lifespans, and easy maintenance.

Benefits

- Durability
- Uniform light distribution
- Energy Savings
- Easy Installation & Maintenance

Applications

- Office
- Warehouse
- Hotel
- Shop
- Other demanding environments

LUXPOINT® LED Batten - Dalbert

Technical Data

Optical Specifications

Wattage		18W	24W	36W	45W
Luminous Flux @CCT	3000K	1710lm	2280lm	3420lm	4275lm
	4000K	1800lm	2400lm	3600lm	4500lm
	6500K	1800lm	2400lm	3600lm	4500lm
Total luminous flux of contained light sources @CCT	3000K	2000lm	2600lm	4000lm	5200lm
	4000K	2100lm	2700lm	4100lm	5300lm
	6500K	2100lm	2700lm	4100lm	5300lm
Efficacy		95-100lm/W	95-100lm/W	95-100lm/W	95-100lm/W
Flickering metric (Pst LM)		<1	<1	<1	<1
Stroboscope effect metric (SVM)		<0.4	<0.4	<0.4	<0.4
CRI		≥80	≥80	≥80	≥80
SDCM		< 6	< 6	< 6	< 6
Beam Angle		120°			
Photobiological safety group acc. To EN62778		RG0	RG0	RG0	RG0
Photobiological safety group acc. To EN62471		RG0	RG0	RG0	RG0
Dimmable		No	No	No	No

Electrical and Mechanical Specifications

Input Voltage		220-240V ~50/60Hz			
Nominal Current		140mA	170mA	210mA	230mA
Inrush current time Th50		100µs@25A	4µs@25A	150µs@25A	150µs@25A
Power Factor		0.5	0.5	0.9	0.9
Max. number of luminaires per miniature circuit breaker	B16	37	75	33	30
	C10	30	47	26	24
	C16	48	75	42	38
Protection class		Class II	Class II	Class II	Class II
Dimensions		L 545mm	L 845mm	L 1145mm	L 1445mm
		W 63mm	W 63mm	W 63mm	W 63mm
		H 28mm	H 28mm	H 28mm	H 28mm
Weight		169g	255g	298g	385g
Housing		Polycarbonate(PC)			
Diffuser		Polystyrene (PS)			
Replaceable light source		No			
Replaceable Control gear		No			
Glow wire test according to IEC60695-2-12		650°C			






System Specifications

Power	AC mains
Operating Temperature	-20°C ~ 40°C
Storage Temperature	-40°C ~ 70°C
Lifespan L70/B50 at 40°C	15000 hours
Lifespan L70/B50 at 25°C	30,000 hours
Number of switching cycles	15,000
Environment	Indoor
Safety Approval	CE, UKCA, RoHS
Mercury content	0.0mg
Warranty	3 years

LUXPOINT® LED Batten - Dalbert

Dimension (Unit: mm)

Class I



Due to the special conditions of manufacturing process of LED, the typical data of technical parameters can only reflect statistical figures and do not necessarily correspond to the actual parameters of each single product which could differ from typical data.

Exceeding maximum ratings for operation voltage will cause hazardous overload and will likely destroy the LED module.

Exceeding maximum ratings for operation and storage temperature will reduce expected life time or destroy the LED module.

Specifications are subject to change without notice. Errors and omission excepted, always make sure to use the most recent release.

LUXPOINT® LED Batten - Dalbert

Ordering codes

Model No.	Wattage	CCT	Fixture Lumen	Light Source Lumen	Size(mm)	Item code	EAN-13
LP BA V01 18W 830 SF 600	18W	3000K	1710lm	2000lm	545x63x28	TXGL25100026155	4897135736913
LP BA V01 18W 840 SF 600	18W	4000K	1800lm	2100lm	545x63x28	TXGL25100026255	4897135736920
LP BA V01 18W 865 SF 600	18W	6500K	1800lm	2100lm	545x63x28	TXGL25100026355	4897135736937
LP BA V01 24W 830 SF 900	24W	3000K	2280lm	2600lm	845x63x28	TXGL26100133355	4895271102579
LP BA V01 24W 840 SF 900	24W	4000K	2400lm	2700lm	845x63x28	TXGL26100133455	4895271102586
LP BA V01 24W 865 SF 900	24W	6500K	2400lm	2700lm	845x63x28	TXGL26100133555	4895271102593
LP BA V01 36W 830 SF 1200	36W	3000K	3420lm	4000lm	1145x63x28	TXGL25100026455	4897135736944
LP BA V01 36W 840 SF 1200	36W	4000K	3600lm	4100lm	1145x63x28	TXGL25100026555	4897135736951
LP BA V01 36W 865 SF 1200	36W	6500K	3600lm	4100lm	1145x63x28	TXGL25100026655	4897135736968
LP BA V01 45W 830 SF 1500	50W	3000K	4275lm	5200lm	1445x63x28	TXGL25100026755	4897135736975
LP BA V01 45W 840 SF 1500	50W	4000K	4500lm	5300lm	1445x63x28	TXGL25100026855	4897135736982
LP BA V01 45W 865 SF 1500	50W	6500K	4500lm	5300lm	1445x63x28	TXGL25100026955	4897135736999

Service contact:
Traxon Technologies Ltd.
Room 1604, 16/F, First Group Centre, 23 Wang Chiu Road,
Kowloon Bay, Kowloon, Hong Kong, China
www.traxon-ecue.com

Traxon Technologies Europe GmbH
Im Dörener Feld 8, 33100 Paderborn, Germany